

**FEDERALLY ENFORCEABLE STATE
OPERATING PERMIT (FESOP) RENEWAL
OFFICE OF AIR QUALITY**

**Reliance Electric
2755 Michigan Road
Madison, Indiana 47250**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F 077-14124-00006	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date:

TABLE OF CONTENTS

SECTION A	SOURCE SUMMARY	4
A.1	General Information [326 IAC 2-8-3(b)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]	
A.4	FESOP Applicability [326 IAC 2-8-2]	
A.5	Prior Permit Conditions	
SECTION B	GENERAL CONDITIONS	7
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-8-1]	
B.3	Permit Term [326 IAC 2-8-4(2)]	
B.4	Enforceability [326 IAC 2-8-6]	
B.5	Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]	
B.6	Severability [326 IAC 2-8-4(4)]	
B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.8	Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]	
B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.10	Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]	
B.11	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]	
B.12	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.13	Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]	
B.14	Emergency Provisions [326 IAC 2-8-12]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination	
B.17	Permit Renewal [326 IAC 2-8-3(h)]	
B.18	Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]	
B.19	Operational Flexibility [326 IAC 2-8-15]	
B.20	Permit Revision Requirement [326 IAC 2-8-11.1]	
B.21	Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2]	
B.22	Transfer of Ownership or Operational Control [326 IAC 2-8-10]	
B.23	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16]	
SECTION C	SOURCE OPERATION CONDITIONS	17
	Emission Limitations and Standards [326 IAC 2-8-4(1)]	
C.1	Overall Source Limit [326 IAC 2-8]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Operation of Equipment [326 IAC 2-8-5(a)(4)]	
C.7	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61 Subpart M]	
	Testing Requirements [326 IAC 2-8-4(3)]	
C.8	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.9	Compliance Requirements [326 IAC 2-1.1-11]	

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 3 of 43
OP No. F 007-14124-00006

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- C.10 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.11 Maintenance of Emission Monitoring Equipment [326 IAC 2-8-4(3)(A)(iii)]
- C.12 Monitoring Methods [326 IAC 3] [40 CFR 60][40 CFR 63]

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- C.13 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]
- C.14 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4, 5]
- C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4, 5]

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

- C.16 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]
- C.17 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS: Surface Coating 24

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.1.1 Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-8-4]
- D.1.2 Volatile Organic Compound Limit (VOC) [326 IAC 2-8-4]
- D.1.3 Particulate Matter (PM) [326 IAC 6-3-2]
- D.1.4 PM₁₀ Limit [326 IAC 2-8-4]
- D.1.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.1.6 Hazardous Air Pollutants (HAPs)
- D.1.7 Volatile Organic Compounds (VOC)
- D.1.8 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- D.1.9 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.1.10 Record Keeping Requirements
- D.1.11 Reporting Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS: Insignificant Activities 27

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.2.1 Particulate Matter (PM) [326 IAC 6-3-2]

Certification 28

Emergency Occurrence Report 29

Quarterly Report 31

Quarterly Deviation and Compliance Monitoring Report 34

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary electric motor manufacturing source.

Authorized Individual:	Dale Minor
Source Address:	2755 Michigan Road, Madison, Indiana 47250
Mailing Address:	2755 Michigan Road, Madison, Indiana 47250
General Source Phone Number:	812-273-1664
SIC Code:	3621
County Location:	Jefferson
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Federally Enforceable State Operating Permit (FESOP) Minor Source, under PSD Rules; Minor Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary operating source consists of the following emission units and pollution control devices:

- (a) One (1) spray booth, known as Paint Booth #1, exhausted to S-17, equipped with dry filters for particulate matter control, capacity: 180 motors per hour.
- (b) Two (2) spray booths, known as Paint Booth #2 and #6, exhausted to S-18 and S-23 respectively, equipped with dry filters for particulate matter control, capacity: 82 motors per hour, each.
- (c) Five (5) spray booths, known as Paint Booth #3, #4, #5, #7 and #8 exhausted to S-12, S-13, S-14, S-15 and S-9 respectively, equipped with dry filters for particulate matter control, capacity: 57 motors per hour, each.
- (d) One (1) hand dip oven, known as Hand Dip Oven #1, exhausted to S-32, capacity: 2.54 stators per hour.
- (e) Two (2) hand dip ovens, known as Hand Dip Oven #2 & #3, exhausted to S-33 and S-34 respectively, capacity: 5.08 stators, total.
- (f) One (1) hand dip bath, known as Hand Dip Bath #1, exhausted to S-36, capacity: 2.54 stators per hour.
- (g) One (1) roll coating system, known as Lead Wire Marking, capacity: 200 wire leads per hour.
- (h) Two (2) dip and spins, known as Dip and Spin #1 and #2, installed in 1996, exhausted to S-1 and S-2 respectively, capacity: 42 motors per hour, each.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment.
- (b) Any of the following structural steel and bridge fabrication activities: Using 80 tons or less of welding consumables.
- (c) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.
- (d) Rotor casting operation, known as Dept. 716-S/V-35, capacity: 270 pounds per hour aluminum.
- (e) Space heaters, process heaters, or boilers using the following fuels: Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) British thermal units per hour.
- (f) Space heaters, process heaters, or boilers using the following fuels: Propane for liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) British thermal units per hour.
- (g) The following VOC and HAP storage containers: Vessels storing lubricating oil, hydraulic oils, machining oils, and machining fluids.
- (h) Machining where an aqueous cutting coolant continuously floods the machining interface.
- (i) Cleaners and solvents characterized as follows:
 - (1) having a vapor pressure equal to or less than 2 kiloPascals; 15 millimeters of mercury; or 0.3 pounds per square inch measured at 38EC (100EF) or;
 - (2) having a vapor pressure equal to or less than 0.7 kiloPascals; 5 millimeters of mercury; or 0.1 pounds per square inch measured at 20EC (68EF); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.
- (j) Infrared cure equipment.
- (k) Solvent recycling systems with batch capacity less than or equal to 100 gallons.
- (l) Paved and unpaved roads and parking lots with public access.
- (m) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and fluid handling equipment.

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 7 of 43
OP No. F 007-14124-00006

- (n) Blowdown for any of the following: sight glass; boiler; compressors; pumps; and cooling tower.
- (o) On-site fire and emergency response training approved by the department.
- (p) Other activities or categories not previously identified:
 - (1) 0.47 million British thermal units per hour natural gas or propane-fired rotor insert, known as Dept. 716-S/V-17.
 - (2) 0.14 million British thermal units per hour natural gas or propane-fired rotor cast torch known as Dept. 716-S/V-35.
 - (3) 1.88 million British thermal units per hour natural gas or propane-fired smelting furnace, known as Dept. 716-S/V-37.
 - (5) Two (2) dip and spins, known as Dip and Spin #3 and #4, installed in 1998, exhausted to S-25, capacity: 42 motors per hour, each.
 - (6) One (1) dip and spin, known as Dip and Spin #5, installed in 1999, exhausted to S-27, capacity: 42 motors per hour.

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) for a Federally Enforceable State Operating Permit (FESOP) Renewal.

A.5 Prior Permit Conditions

- (a) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued.

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [IC 13]

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

B.2 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

B.3 Permit Term [326 IAC 2-8-4(2)]

This permit is issued for a fixed term of five (5) years from the original date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.4 Enforceability [326 IAC 2-8-6]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.6 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)] [326 IAC 2-8-5(a)(4)]

(a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking

and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit or, for information claimed to be confidential, the Permittee may furnish such records directly to the U. S. EPA along with a claim of confidentiality.[326 IAC 2-8-4(5)(E)]

- (c) The Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit, except those specifically designated as not federally enforceable, is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; and
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- (c) An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification covered

the time period from the date of the first original final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.13 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,
Telephone No.: 317-233-5674 (ask for Compliance Section)
Facsimile No.: 317-233-5967

Failure to notify IDEM, OAQ by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and

(C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(6) The Permittee immediately took all reasonable steps to correct the emergency.

(c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

(d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.

(e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.

(f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.

(g) Operations may continue during an emergency only if the following conditions are met:

(1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

(2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:

(A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and

(B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent.

Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report.

The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
 - (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) Failure to implement elements of the Preventive Maintenance Plan unless such failure has caused or contributed to a deviation.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Emergencies shall be included in the Quarterly Deviation and Compliance Monitoring Report.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.17 Permit Renewal [326 IAC 2-8-3(h)]

-
- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
 - (2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]

If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as needed to process the application.

B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.19 Operational Flexibility [326 IAC 2-8-15]

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-8-15(b), (c)(1), and (d).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional conditions:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) Emission Trades [326 IAC 2-8-15(c)]

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

- (d) Alternative Operating Scenarios [326 IAC 2-8-15(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

B.20 Permit Revision Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed 326 IAC 2 and 326 IAC 2-8-11.1.

B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 19 of 43
OP No. F 007-14124-00006

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-11(b)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAQ, Technical Support and Modeling Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emissions Limitations and Standards [326 IAC 2-8-4(1)]

C.1 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

(a) Pursuant to 326 IAC 2-8:

- (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)).
- (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
- (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.

(b) Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)), emissions of particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period.

(c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.

(d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment is are in operation.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality

100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited, pursuant to the provisions of 40 CFR 61, Subpart M, is federally enforceable.

Testing Requirements [326 IAC 2-8-4(3)]

C.8 Performance Testing [326 IAC 3-6]

-
- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.10 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented upon permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.11 Maintenance of Emission Monitoring Equipment [326 IAC 2-8-4(3)(A)(iii)]

- (a) In the event that a breakdown of the emission monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no often less than once an hour until such time as the continuous monitor is back in operation.
- (b) The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.

C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing performed required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.13 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and

All documents submitted pursuant to this condition shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

C.14 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. The compliance monitoring plan can be either an entirely new document, consist in whole of information contained in other documents, or consist of a combination of new

information and information contained in other documents. If the compliance monitoring plan incorporates by reference information contained in other documents, the Permittee shall identify as part of the compliance monitoring plan the documents in which the information is found. The elements of the compliance monitoring plan are:

- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAQ, upon request and shall be subject to review and approval by IDEM, OAQ. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of:
 - (A) Reasonable response steps that may be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking reasonable response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to take reasonable response steps may constitute a violation of the permit.
- (c) Upon investigation of a compliance monitoring excursion, the Permittee is excused from taking further response steps for any of the following reasons:
- (1) A false reading occurs due to the malfunction of the monitoring equipment. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met

and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

- (e) All monitoring required in Section D shall be performed at all times the equipment is operating. If monitoring is required by Section D and the equipment is not operating, then the Permittee may record the fact that the equipment is not operating or perform the required monitoring.
- (f) At its discretion, IDEM may excuse the Permittee's failure to perform the monitoring and record keeping as required by Section D, if the Permittee provides adequate justification and documents that such failures do not exceed five percent (5%) of the operating time in any quarter. Temporary, unscheduled unavailability of qualified staff shall be considered a valid reason for failure to perform the monitoring or record keeping requirements in Section D.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.16 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.17 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and

Compliance Monitoring Report shall include the certification by the “authorized individual” as defined by 326 IAC2-1.1-1(1).

- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the “authorized individual” as defined by 326 IAC 2-1.1-1(1).
- (e) The first report covered the time period commencing on the date of issuance of original FESOP and ending on the last day of the reporting period. All subsequent reporting periods shall be based on calendar years.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

- (a) One (1) spray booth, known as Paint Booth #1, exhausted to S-17, equipped with dry filters for particulate matter control, capacity: 180 motors per hour.
- (b) Two (2) spray booths, known as Paint Booth #2 and #6, exhausted to S-18 and S-23 respectively, equipped with dry filters for particulate matter control, capacity: 82 motors per hour, each.
- (c) Five (5) spray booths, known as Paint Booth #3, #4, #5, #7 and #8 exhausted to S-12, S-13, S-14, S-15 and S-9 respectively, equipped with dry filters for particulate matter control, capacity: 57 motors per hour, each.
- (d) One (1) hand dip oven, known as Hand Dip Oven #1, exhausted to S-32, capacity: 2.54 stators per hour.
- (e) Two (2) hand dip ovens, known as Hand Dip Oven #2 & #3, exhausted to S-33 and S-34 respectively, capacity: 5.08 stators, total.
- (f) One (1) hand dip bath, known as Hand Dip Bath #1, exhausted to S-36, capacity: 2.54 stators per hour.
- (g) One (1) roll coating system, known as Lead Wire Marking, capacity: 200 wire leads per hour.
- (h) Two (2) dip and spins, known as Dip and Spin #1 and #2, installed in 1996, exhausted to S-1 and S-2 respectively, capacity: 42 motors per hour, each.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.1.1 Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-8-4]

- (a) An individual HAP delivered to the coating applicators in Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall not exceed nine (9.0) tons per twelve (12) consecutive month period. Therefore, the requirements of 326 IAC 2-7 are not applicable.
- (b) The combination of HAPs delivered to the coating applicators in Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall not exceed twenty-four (24.0) tons per twelve (12) consecutive month period. Therefore, the requirements of 326 IAC 2-7 are not applicable.

D.1.2 Volatile Organic Compounds (VOC) Limit [326 IAC 2-8-4]

The volatile organic compounds (VOCs) delivered to the applicators in Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2, including cleanup solvents shall not exceed a total of 98.0 tons per twelve (12) consecutive month period. Therefore the requirements of 326 IAC 2-7 are not applicable.

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 30 of 43
OP No. F 007-14124-00006

D.1.3 Particulate Matter (PM) [326 IAC 6-3-2]

The particulate matter (PM) from Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour.}$$

D.1.4 PM₁₀ [326 IAC 2-8-4]

Any change or modification which may increase potential to emit PM₁₀ from the entire source to one hundred (100) tons per year or more shall require approval from IDEM, OAQ prior to making the change.

D.1.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.1.6 Volatile Organic Compounds (VOCs) and Hazardous Air Pollutants (HAPs)

Compliance with the HAP and VOC usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer.

D.1.7 HAP and VOC Emissions

Compliance with Condition D.1.1 and D.1.2 shall be demonstrated within 30 days of the end of each month based on the total volatile organic compound usage for the twelve (12) month period.

D.1.8 Particulate Matter (PM)

The dry filters for PM control shall be in operation at all times when Paint Booths #1- #8 are in operation.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.9 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks SV11, 12, 28, 39, 40, 42, 44 and 45 while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation

of this permit.

- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.10 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC and HAP usage limits and/or the VOC and HAP emission limits established in Condition D.2.2 and D.2.2.
 - (1) The amount and HAP and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC and HAP usage for each month; and
 - (5) The weight of VOCs and HAPs emitted for each compliance period.
- (b) To document compliance with Condition D.1.9, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.11 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment.
- (b) Any of the following structural steel and bridge fabrication activities: Using 80 tons or less of welding consumables.
- (c) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.
- (d) Rotor casting operation, known as Dept. 716-S/V-35, capacity: 270 pounds per hour aluminum.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.2.1 Particulate Matter (PM) [326 IAC 6-3-2]

The particulate matter (PM) from the brazing equipment, cutting torches soldering equipment, welding equipment and grinding and machining operations shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

Any control device shall be in operation at all times the grinding and machining are in operation, in order to comply with this limit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
CERTIFICATION**

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006

**This certification shall be included when submitting monitoring, testing reports/results
or other documents as required by this permit.**

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Affidavit (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
EMERGENCY OCCURRENCE REPORT**

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006

This form consists of 2 pages

Page 1 of 2

- 9** This is an emergency as defined in 326 IAC 2-7-1(12)
 (The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
 (The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency:

Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 37 of 43
OP No. F 007-14124-00006

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006
Facility: Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2
Parameter: VOC
Limit: 98.0 tons per twelve consecutive month period

YEAR: _____

Month	VOC (tons)	VOC (tons)	VOC (tons)
	This Month	Previous 11 Months	12 Month Total

9No deviation occurred in this quarter.

9Deviation/s occurred in this quarter.

Deviation has been reported on:

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

Reliance Electric
Madison, Indiana
Permit Reviewer: PMC/MES

Page 39 of 43
OP No. F 007-14124-00006

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006
Facility: Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2
Parameter: Single HAP
Limit: 9.0 tons per twelve consecutive month period

YEAR: _____

Month	Single HAP (tons)	Single HAP (tons)	Single HAP (tons)
	This Month	Previous 11 Months	12 Month Total

9No deviation occurred in this quarter.

9Deviation/s occurred in this quarter.

Deviation has been reported on:

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006
Facility: Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2
Parameter: Combination of HAPs
Limit: 24.0 tons per twelve consecutive month period

YEAR: _____

Month	Combination of HAPs	Combination of HAPs	Combination of HAPs
	This Month	Previous 11 Months	12 Month Total

9No deviation occurred in this quarter.

9Deviation/s occurred in this quarter.

Deviation has been reported on:

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Reliance Electric
Source Address: 2755 Michigan Road, Madison Indiana 47250
Mailing Address: 2755 Michigan Road, Madison Indiana 47250
FESOP No.: F 077-14124-00006

Months: _____ to _____ Year: _____

Page 1 of 2

This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

9 No deviation occurred in this quarter.

9 Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Form Completed By: _____

Title/Position: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

Indiana Department of Environmental Management
Office of Air Quality

Technical Support Document (TSD)
for a Federally Enforceable State Operating Permit (FESOP) Renewal

Source Background and Description

Source Name:	Reliance Electric
Source Location:	2755 Michigan Road, Madison, Indiana 47250
County:	Jefferson
SIC Code:	3621
Operation Permit No.:	F 077-14124-00006
Permit Reviewer:	Paula M. Cognitore

The Office of Air Quality (OAQ) has reviewed a FESOP renewal application from Reliance Electric relating to the operation of an electric motor manufacturing source. The original FESOP 077-6638-00006, issued on December 11, 1999, expires December 11, 2001.

Permitted and/or Exempt Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) spray booth, known as Paint Booth #1, exhausted to S-17, equipped with dry filters for particulate matter control, capacity: 180 motors per hour.
- (b) Two (2) spray booths, known as Paint Booth #2 and #6, exhausted to S-18 and S-23 respectively, equipped with dry filters for particulate matter control, capacity: 82 motors per hour, each.
- (c) Five (5) spray booths, known as Paint Booth #3, #4, #5, #7 and #8 exhausted to S-12, S-13, S-14, S-15 and S-9 respectively, equipped with dry filters for particulate matter control, capacity: 57 motors per hour, each.
- (d) One (1) hand dip oven, known as Hand Dip Oven #1, exhausted to S-32, capacity: 2.54 stators per hour.
- (e) Two (2) hand dip ovens, known as Hand Dip Oven #2 & #3, exhausted to S-33 and S-34 respectively, capacity: 5.08 stators, total.
- (f) One (1) hand dip bath, known as Hand Dip Bath #1, exhausted to S-36, capacity: 2.54 stators per hour.
- (g) One (1) roll coating system, known as Lead Wire Marking, capacity: 200 wire leads per hour.

- (h) Two (2) dip and spins, known as Dip and Spin #1 and #2, installed in 1996, exhausted to S-1 and S-2 respectively, capacity: 42 motors per hour, each.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities proposed at this source during this review process.

New Emission Units and Pollution Control Equipment Receiving Prior Approval

There are no new facilities proposed at this source during this review process.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment.
- (b) Any of the following structural steel and bridge fabrication activities: Using 80 tons or less of welding consumables.
- (c) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.
- (d) Rotor casting operation, known as Dept. 716-S/V-35, capacity: 270 pounds per hour aluminum.
- (e) Space heaters, process heaters, or boilers using the following fuels: Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) British thermal units per hour.
- (f) Space heaters, process heaters, or boilers using the following fuels: Propane for liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) British thermal units per hour.
- (g) The following VOC and HAP storage containers: Vessels storing lubricating oil, hydraulic oils, machining oils, and machining fluids.
- (h) Machining where an aqueous cutting coolant continuously floods the machining interface.
- (i) Cleaners and solvents characterized as follows:
 - (1) having a vapor pressure equal to or less than 2 kilopascals; 15 millimeters of mercury; or 0.3 pounds per square inch measured at 38EC (100EF) or;
 - (2) having a vapor pressure equal to or less than 0.7 kilopascals; 5 millimeters of mercury; or 0.1 pounds per square inch measured at 20EC (68EF); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.

- (j) Infrared cure equipment.
- (k) Solvent recycling systems with batch capacity less than or equal to 100 gallons.
- (l) Paved and unpaved roads and parking lots with public access.
- (m) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and fluid handling equipment.
- (n) Blowdown for any of the following: sight glass; boiler; compressors; pumps; and cooling tower.
- (o) On-site fire and emergency response training approved by the department.
- (p) Other activities or categories not previously identified:
 - (1) 0.47 million British thermal units per hour natural gas or propane-fired rotor insert, known as Dept. 716-S/V-17.
 - (2) 0.14 million British thermal units per hour natural gas or propane-fired rotor cast torch known as Dept. 716-S/V-35.
 - (3) 1.88 million British thermal units per hour natural gas or propane-fired smelting furnace, known as Dept. 716-S/V-37.
 - (5) Two (2) dip and spins, known as Dip and Spin #3 and #4, installed in 1998, exhausted to S-25, capacity: 42 motors per hour, each.
 - (6) One (1) dip and spin, known as Dip and Spin #5, installed in 1999, exhausted to S-27, capacity: 42 motors per hour.

Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following:

F 077-6638-00006, issued December 1996.

All conditions from previous approvals were incorporated into this FESOP except the following:

- (1) F 077-6638-00006, issued December 1996

Condition D.1.1: The volatile organic compound (VOC) emissions from the eight (8) paint booths (PB#1, PB#2, PB#3, PB#4, PB#5, PB#6, PB#7, and PB#8), three (3) hand dip ovens (HDO#1, HDO#2, and HDO#3), two (2) hand dip baths (HDB#1 and HDB#5), one (1) roll coating booth, one (1) natural gas or propane fired oven with hand dip surface coating application, and one (1) epoxy resin (dipping) system shall not exceed 8.17 tons per month. Therefore, the requirements of 326 IAC 2-7 do not apply.

The condition has been changed to the following:

D.1.2 Volatile Organic Compounds (VOC) Limit [326 IAC 2-8-4]

The volatile organic compounds (VOCs) delivered to the applicators in Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2, including cleanup solvents shall not exceed 98.0 tons per twelve (12) consecutive month period. Therefore the requirements of 326 IAC 2-7 are not applicable.

(2) F 077-6638-00006, issued December 1996

Condition D.1.2:

- (A) The amount of any single hazardous air pollutant (HAP) delivered to the applicators, hand dip ovens, hand dip baths, roll coating booth, natural gas or propane fired oven with hand dip surface coating application and epoxy resin (dipping) system shall not exceed 0.75 tons per month.
- (B) The amount of any combination of HAPs delivered to the applicators, hand dip ovens, hand dip baths, roll coating booth, natural gas or propane fired oven with hand dip surface coating application and epoxy resin (dipping) systems shall not exceed 2.00 tons per month

The condition has been changed to the following:

Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-8-4]

- (A) An individual HAP delivered to the coating applicators in Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall not exceed nine (9.0) tons per twelve (12) consecutive month period. Therefore, the requirements of 326 IAC 2-7 are not applicable.
- (B) The combination of HAPs delivered to the coating applicators Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall not exceed less than twenty-four (24.0) tons per twelve (12) consecutive month period. Therefore, the requirements of 326 IAC 2-7 are not applicable.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the FESOP renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP renewal application for the purposes of this review was received on March 9, 2001. The application was received timely, more than nine (9) months before the December 11, 2001 expiration of the original FESOP.

Emission Calculations

See pages 1 through 2 of Appendix A of this document for detailed emissions calculations.

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

The source, issued a FESOP on December 11, 1996 has opted to continue with their FESOP status, rather than applying for a Part 70 Operating Permit. Therefore, the following table also reflects the PTE after all FESOP limitations.

Pollutant	Potential To Emit (tons/year)
PM	5.91
PM ₁₀	5.91
SO ₂	2.0
VOC	less than 100
CO	2.0
NO _x	2.0

Note: For the purpose of determining Title V applicability for particulates, PM₁₀, not PM, is the regulated pollutant in consideration.

HAPs	Potential To Emit (tons/year)
Xylene	2.55
MIBK	0.706
Ethyl Benzene	0.781
Glycol Ethers	less than 10
Naphthalene	0.059
TOTAL	less than 25

This source, otherwise required to obtain a Title V permit, agreed to accept a permit with federally enforceable limits that restrict its PTE to below the Title V emission levels. Therefore, this source was issued a Federally Enforceable State Operating Permit (FESOP), pursuant to 326 IAC 2-8. The source will continue to comply with the requirements of 326 IAC 2-8, FESOP.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 1993

OAQ emission data.

Pollutant	Actual Emissions (tons/year)
PM	0.000
PM ₁₀	0.000
SO ₂	0.0018
VOC	0.000
CO	0.060
NO _x	0.300
HAP	not listed

Potential to Emit After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Federally Enforceable State Operating Permit.

	Limited Potential to Emit (tons/year)						
Process/facility	PM	PM ₁₀	SO ₂	VOC	CO	NO _x	HAPs
Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2	0.910	0.910	0.00	less than 98.0	0.00	0.00	Single less than 9.0 Total less than 24.0
Insignificant Activities	5.0	5.0	2.0	2.0	2.0	2.0	1.0
Total Emissions	5.91	5.91	2.0	less than 100	2.0	2.0	Single less than 10 Total less than 25

County Attainment Status

The source is located in Jefferson County.

Pollutant	Status
PM ₁₀	Attainment
SO ₂	Attainment
NO ₂	Attainment

Pollutant	Status
Ozone	Attainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Jefferson County has been designated as attainment or unclassifiable for ozone.
- (b) Jefferson County has been classified as attainment or unclassifiable for all remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Federal Rule Applicability

- (a) There are still no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 2-6 (Emission Reporting)

This source is located in Jefferson County and the potential to emit VOC is limited to less than one hundred (100) tons per year. The source is not one of the twenty-eight (28) listed sources and its potential to emit PM₁₀ is less than one hundred (100) tons per year, including fugitive emissions, therefore, 326 IAC 2-6 still does not apply.

326 IAC 2-8-4 (FESOP)

Pursuant to this rule, the amount of PM₁₀, SO₂, VOC, CO and NO_x shall be limited to less than one hundred (100) tons per year. In addition, the amount of a single HAP shall be limited to less than ten (10) tons per year and the combination of all HAPs shall be limited to less than twenty-five (25) tons per year. Therefore, the requirements of 326 IAC 2-7, still do not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity limitations), except as provided in 326 IAC 5-1-3 (Temporary alternative opacity limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR Part 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity

monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

The dry filters shall be in operation at all times Paint Booth #1- #8 are in operation, in order to comply with this limit.

326 IAC 8-2 (Surface Coating Emission Limitations)

The surface coating of motor parts at the source was constructed before 1980 in Jefferson County. Therefore specific 326 IAC 8-2 rules do not apply.

326 IAC 8-6 (Organic Solvent Limitations)

The requirements of 326 IAC 8-6 could apply to surface coating of electric motor parts, however the FESOP limitation of less than 100 tons per year of VOC emissions makes the 326 IAC 8-6 requirements not applicable.

State Rule Applicability - Insignificant Activities

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the brazing equipment, cutting torches, soldering equipment, welding equipment, grinding and machining operations and rotor casting shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

Any control device shall be in operation at all times the grinding and machining are in operation, in order to comply with this limit.

Testing Requirements

No testing is required for the emissions from Paint Booth #1- #8, Hand Dip Oven #1-#3, Hand Bath #1, Lead Wire Marking, Dip and Spin #1 and #2. All emissions are based on the material usage and MSDS for each material.

Reliance Electric
Madison, Indiana
Permit Reviewer:MES

Page 10 of 12
F 077-14124-00006

Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The previous compliance monitoring requirements applicable to this source are retained as follows:

The dry filters used for PM control in Paint Booth #1-#8 have applicable compliance monitoring conditions as specified below:

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters for Paint Booth #1-#8. To monitor the performance of the dry filters, weekly observations shall be made of the overspray while Paint Booth #1- #8 is in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the spray booth stack exhausts, known as Stacks SV11, 12, 28, 39, 40, 42, 44 and 45, for the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an overspray emission, evidence of overspray emission, or other abnormal emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit..
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

The dry filters must operate properly to ensure compliance with 326 IAC 6-3-2 and 326 IAC 2-8 (FESOP).

Conclusion

The operation of this electric motor manufacturing source shall be subject to the conditions of the

Reliance Electric
Madison, Indiana
Permit Reviewer:MES

Page 12 of 12
F 077-14124-00006

attached proposed FESOP Renewal No.: F 077-14124-00006.

**Appendix A: Emissions Calculations
VOC and Particulate
From Surface Coating Operations**

**Company Name: Reliance Electric
Address City IN Zip: 2755 Michigan Road, Madision, Indiana 47250
FESOP: F 077-14124
Plt ID: 077-00006
Reviewer: Paula M Cognitore
Date: March 9, 2001**

Material	Density (lbs/gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (units/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC (pounds per hour)	Potential VOC (pounds per day)	Potential VOC (tons per year)	Particulate Potential (tons/yr)	lbs VOC/gal solids	Transfer Efficiency
Spray Booth #1																
EXWAE001S Enamel (S-126)	9.20	23.78%	0.0%	23.8%	0.0%	87.52%	0.02000	180.000	2.19	2.19	7.88	189.02	34.50	27.64	2.50	75%
Spray Booth #2																
C-647 Hardener (G-10)	7.56	82.00%	0.0%	82.0%	0.0%	0.00%	0.00100	82.000	6.20	6.20	0.51	12.20	2.23			
Green Epoxy (G-12)	8.19					30.00%	0.00100	82.000						0.74		75%
Spray Booth #3																
EXWAE001S Enamel (S-126)	9.20	23.78%	0.0%	23.8%	0.0%	87.52%	0.02000	57.000	2.19	2.19	2.49	59.86	10.92	8.75	2.50	75%
Spray Booth #4																
WB 35 Gloss Black Epoxy (T-51)	9.92	21.70%	0.0%	21.7%	0.0%	0.00%	0.02000	57.000	2.15	2.15	2.45	58.90	10.75			
4824-3-APX Blue Green Epoxy (T-52)	10.51					86.68%	0.02000	57.000						13.12		75%
Spray Booth #5																
WB White Epoxy (T-51)	10.63					84.85%	0.02000	57.000						13.27		75%
WB 35 Gloss Black Epoxy (T-63)	9.92	21.70%	0.0%	21.7%	0.0%	0.00%	0.02000	57.000	2.15	2.15	2.45	58.90	10.75			
Spray Booth #6																
Green Epoxy (G-012)	8.19					30.00%	0.00100	82.000						0.74		75%
C-647 Hardener (G-10)	7.56	82.00%	0.0%	82.0%			0.00100	82.000	6.20	6.20	0.51	12.20	2.23	0.49		
Spray Booth #7																
4824-3-APX Blue Green Epoxy (T-52)	10.51					86.68%	0.02000	57.000						13.12		75%
75% PM Solvent (T-053)	7.85	98.00%	0.0%	98.0%	0.0%	0.00%	0.02000	57.000	7.69	7.69	8.77	210.48	38.41			
Spray Booth #8																
WB Black HCP (94824-3-AXG) (T050)	10.09	20.30%	0.0%	20.3%	0.0%	0.00%	0.02000	57.000	2.05	2.05	2.34	56.04	10.23			
4824-3-APX Blue Green Epoxy (T-52)	10.51					86.68%	0.02000	57.000						13.12		75%
Hand Dip Bath																
Sterling U475HER (S-53)	8.78	39.00%	0.0%	39.0%	0.0%	54.00%	0.00240	2.540	3.42	3.42	0.02	0.50	0.09	0.00	6.34	100%
Hand Dip Oven #1																
Sterling U475HER (S-53)	8.78	39.00%	0.0%	39.0%	0.0%	0.00%	0.00240	2.540	3.42	3.42	0.02	0.50	0.09	0.00		100%
Hand Dip Ovens #2 and #3																
Sterling U475HER (S-53)	8.78	39.00%	0.0%	39.0%	0.0%	54.00%	0.00240	5.080	3.42	3.42	0.04	1.00	0.18	0.00	6.34	100%
One Roll Coating System																
Gem type HCP Standard Ink Extender (G-007)	7.30	100.00%	0.0%	100.0%	100.0%	0.00%	0.00004	200.000	ERR	7.30	0.06	1.40	0.26	0.00		100%
Gem Type HCP Standard Black Ink (G-025)	8.50	85.70%	0.0%	85.7%	0.0%	14.30%	0.00004	200.000	7.28	7.28	0.06	1.40	0.26	0.00	50.94	100%
Dip & Spin #1																
ER 134R Thermopoxy Compound (G-39)	9.65	7.00%	0.0%	7.0%	0.0%	93.00%	0.02400	42.000	0.68	0.68	0.68	16.34	2.98	0.00	0.73	100%
Dip & Spin #2																
ER 134R Thermopoxy Compound (G-39)	9.65	7.00%	0.0%	7.0%	0.0%	93.00%	0.02400	42.000	0.68	0.68	0.68	16.34	2.98	0.00	0.73	100%
Dip & Spin #3																
ER 134R Thermopoxy Compound (G-39)	9.65	7.00%	0.0%	7.0%	0.0%	93.00%	0.02400	38.000	0.68	0.68	0.62	14.79	2.70	0.00	0.73	100%
Dip & Spin #4																
ER 134R Thermopoxy Compound (G-39)	9.65	7.00%	0.0%	7.0%	0.0%	93.00%	0.02400	38.000	0.68	0.68	0.62	14.79	2.70	0.00	0.73	100%
Dip & Spin #5																
ER 134R Thermopoxy Compound (G-39)	9.65	7.00%	0.0%	7.0%	0.0%	93.00%	0.02400	38.000	0.68	0.68	0.62	14.79	2.70	0.00	0.73	100%

State Potential Emissions

PM

Control Efficiency
Uncontrolled
Controlled

99.00%

30.8

739

135

91.0
0.910

METHODOLOGY

Worst Case VOC and PM materials for each facility used in calculations

Pounds of VOC per Gallon Coating less Water = (Density (lbs/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lbs/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lbs/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lbs/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lbs/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

**Appendix A: Emission Calculations
HAP Emission Calculations**

Page 2 of 2 TSD AppA

**Company Name: Reliance Electric
Address City IN Zip: 2755 Michigan Road, Madision, Indiana 47250
Part 70: F 077-14124
Plt ID: 077-00006
Reviewer: Paula M Cognitore
Date: March 9, 2001**

Material	Density (lbs/gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Xylene	Weight % MIBK	Weight % Ethyl Benzene	Weight % Glycol Ethers	Weight % Naphthalene	Xylene Emissions (tons/yr)	MIBK Emissions (tons/yr)	Ethyl Benzene Emissions (tons/yr)	Glycol Ethers Emissions (tons/yr)	Naphthalene Emissions (tons/yr)
Spray Booth #1													
EXWAE001S Enamel (S-126)	9.20	0.02000	180.000	0.00%	0.00%	0.00%	10.00%	0.00%	0.00	0.00	0.00	14.51	0.00
Spray Booth #2													
C-647 Hardener (G-10)	7.56	0.00100	82.000	43.00%	0.00%	13.00%	0.00%	0.00%	1.17	0.00	0.35	0.00	0.00
Green Epoxy (G-12)	8.19	0.00100	82.000	0.00%	11.00%	0.00%	7.00%	1.00%	0.00	0.32	0.00	0.21	0.03
Spray Booth #3													
EXWAE001S Enamel (S-126)	9.20	0.02000	57.000	0.00%	0.00%	0.00%	10.00%	0.00%	0.00	0.00	0.00	4.59	0.00
Spray Booth #4													
EXWAE001S Enamel (S-126)	9.20	0.02000	57.000	0.00%	0.00%	0.00%	10.00%	0.00%	0.00	0.00	0.00	4.59	0.00
Spray Booth #5													
EXWAE001S Enamel (S-126)	9.20	0.02000	57.000	0.00%	0.00%	0.00%	10.00%	0.00%	0.00	0.00	0.00	4.59	0.00
Spray Booth #6													
Green Epoxy (G-012)	8.19	0.00100	82.000	0.00%	11.00%	0.00%	7.00%	1.00%	0.00	0.32	0.00	0.21	0.03
C-647 Hardener (G-10)	7.56	0.00100	82.000	43.00%	0.00%	13.00%	0.00%	0.00%	1.17	0.00	0.35	0.00	0.00
Spray Booth #7													
EXWAE001S Enamel (S-126)	9.20	0.02000	57.000	0.00%	0.00%	0.00%	10.00%	0.00%	0.00	0.00	0.00	4.59	0.00
Hand Dip Bath													
Sterling U475HER (S-53)	8.78	0.00240	2.540	23.00%	0.00%	8.00%	17.00%	0.00%	0.05	0.00	0.02	0.04	0.00
Hand Dip Oven #1													
Sterling U475HER (S-53)	8.78	0.00240	2.540	23.00%	0.00%	8.00%	17.00%	0.00%	0.05	0.00	0.02	0.04	0.00
Hand Dip Ovens #2 and #3													
Sterling U475HER (S-53)	8.78	0.00240	5.080	23.00%	0.00%	8.00%	17.00%	0.00%	0.11	0.00	0.04	0.08	0.00
One Roll Coating System													
Gem type HCP Standard Ink Extender (G-007)	7.30	0.00002	200.000	0.00%	45.80%	0.00%	0.00%	0.00%	0.00	0.06	0.00	0.00	0.00
Individual Total									2.55	0.706	0.781	33.5	0.059
Overall Total									37.5				